EZ Limited Finishing Prep Station



- Easy to Install and Operate
- Easy to Add Heat
- Simple to Maintain
- ETL Listed* When Curtains and Control Panel is Purchased

A premium solution for prepping and painting vehicles, Col-Met's EZ Limited Finishing Prep Station draws fresh air from the cleaner upper levels of the shop through a pressurization fan. The air is forced down in the prep station through a filter bank located in the ceiling near the entry. Keeping your shop clean, the air is drawn through the prep station work area into a filtered exhaust plenum at the opposite end and exhausted out to the atmosphere through the exhaust fan and stack. This design allows for easy addition of a heated air makeup unit.




- >> Heavy Duty Construction Hanging intake plenum and exhaust wall plenum are fabricated with 18-guage galvanized steel panels
- >> Superior Lighting Gives bright, full booth illumination from four-tube, 48" long, 32-watt, fluorescent light fixtures. Col-Met light fixtures are ETL listed (Class 1 Division 2, Groups A, B, C, D and Class 2 Division 2, Groups F and G).
- >> Efficient Fans & Motors (1) 18" diameter tubeaxial fan with a 1 ½ HP, three-phase motor.
- >> **Airflow** Modified downdraft and downdraft airflow; Filtered exhaust plenum
- >>> **Supporting Accessories** Panels, assembly hardware, filters, and exhaust fan and stack included
- >>> Meets Quality Standards Complies with NFPA 33 regulations pertaining to limited finishing workstations; All fixtures are ETL listed and approved for their intended use and placement


Options

- >> Goff™ Curtain Walls optional for closing of painting area (installed height is required)
- >> Control panel and other electrical components can be purchased separately
- >> Easy addition of heated air makeup unit









Model Number	Interior Dimensions			Exterior Dimensions			Nominal Door Opening		€-9.	Air Flow	Fan Spec.		Filters	
	Width	Height	Length	Width	Height	Length	Width	Height	Lights	SCFM	Dia.	HP	Int.	Exh.
EPS-14-10-24-P-SB	14'-0"	10'-0"	24'-0"	14'-4"	12'-2"	26'-6"	14'-0"	10'-0"	8	5,000	(2)18"	1.5HP	12	12
Reference Key	Α	В	С											